

Telephone: (44)01827 255719
Email: distributors@img-limited.co.uk
Industrial Maintenance Group Distributors
Riverside Industrial Estate
Fazeley, Tamworth
Staffordshire. B78 3RW

POWER JET DE-ICER

An industrial strength, water free formulation, powerful de-icer spray for de-icing windscreens and locks at temperatures down to - 15°C



What is Power Jet De-Icer?

Power Jet De-Icer is a revolutionary super powered de-icing spray which can extend to heights not achieved by regular de-icers. So windscreens on vans, HGV's and coaches are no longer out of reach.

It's water free industrial strength formulation means that you don't get the dreaded "re-freeze" after spraying.

How does Power Jet De-Icer work?

Power Jet De-Icer has a highly effective, powerful delivery system which can dispense industrial strength de-icer to surfaces which are hard to reach such as HGV, bus and coach windscreens as well as forcing frozen locks back into use.

Unlike conventional de-icers, Power Jet De-Icer has the power to remove hazardous ice even at extreme temperatures.

(use Power Jet De-Icer at temperatures as low as -15°C)

Key features and benefits of Power Jet De-Icer

- Innovative powerful delivery system ensures effective de-icing.
- Use even at extreme temperatures (-15°C).
 Water-free formulation.
- Ideal for use on coaches, buses, HGV's.
- Fantastic for de-icing locks.

How to get the best results

Remove any loose snow and ice build up.

Spray onto the frozen surface.

Repeat as necessary.

Apply a final coat to help prevent re-freezing.

Product Information

Always ensure that precautionary measures found in the MSDS sheet for Power Jet De-Icer are read and followed before use.

IMG Distributors Riverside Ind. Estate, Fazelev, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routhely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.