

Telephone: (44)01827 255719
Email: distributors@img-limited.co.uk
Industrial Maintenance Group Distributors
Riverside Industrial Estate
Fazeley, Tamworth
Staffordshire. B78 3RW

Power Jet De-icer

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product Identifier

Material name : Powerjet De-icer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Water free de-icer for windscreens, hinges, locks and other mechanisms.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: IMG Ltd.,

Unit M

Riverside Industrial Estate

Fazeley Tamworth B78 3RW

Tel. : 01827 283322

Fax. : 01827 250143 Email (for SDSs) : sales@img-limited.co.uk

1.4 Emergency tel. no.: 01827 283322 (Available from 08.30-17.00 hours).

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Physical and Chemical Hazards Flam.Aerosol 1; H222; H229 Human health Eye Irrit.2; H319; STOT SE3, H336

Environment Not classified

2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC

Signal word: Danger Contains: Propan-2-ol Pictogram(s):





H-Statements:	H222 H229 H319	Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation.
	H336	May cause drowsiness or dizziness

P-Statements:	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P211	Do not spray on an open flame or other ignition source.

P251 Pressurised container: Do not pierce or burn, even after use.
P261 Avoid breathing vapour/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P337+313 If eye irritation persists, get medical advice/attention.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards: In use, may form flammable / explosive vapour-air mixture.