









# Damp Guard

## Masonry waterproofing liquid

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.

	<p><b>SECTION 1</b> Product name Description Appearance and odour</p>	<p><b>PRODUCT IDENTIFICATION</b> Damp Guard Masonry waterproofing liquid. Colourless with solvent odour.</p>			
	<p><b>SECTION 2</b></p>	<p><b>HAZARDS IDENTIFICATION</b> Flammable. Harmful: may cause lung damage if swallowed. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.</p>			
	<p><b>SECTION 3</b> <b>Hazardous components</b> <b>Common Chemical Names</b> White Spirit</p>	<p><b>COMPOSITION</b> <b>Related Information</b> <b>% (w/w)</b> &gt;80</p>	<p><b>CAS no.</b> 64742-82-1</p>	<p><b>Classification</b> Xn, N</p>	<p><b>Risk Phrases</b> 10, 65, 66, 67, 51/53</p>
	<p><b>SECTION 4</b> <b>In cases of contact</b> Eyes Ingestion Inhalation Skin</p>	<p><b>FIRST AID MEASURES</b> Flush with water for 15 minutes. Seek medical advice if irritation persists. Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet. Remove to fresh air for at least 10 minutes. Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream. Seek medical advice if irritation develops.</p>			
	<p><b>SECTION 5</b> Extinguishing media Special procedures</p>	<p><b>FIRE FIGHTING MEASURES</b> Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet. Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down.</p>			
	<p><b>SECTION 6</b> Clean-up procedures</p>	<p><b>ACCIDENTAL RELEASE MEASURES</b> Remove all ignition sources. Do not discharge into drains or rivers. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.</p>			
	<p><b>SECTION 7</b> Handling Storage</p>	<p><b>HANDLING AND STORAGE</b> Do not eat, smoke or drink whilst working with this material. Wash hands before meals and after work. Store in a cool, well ventilated area. Keep containers tightly closed.</p>			
	<p><b>SECTION 8</b> <b>Hazardous components</b> Chemical name White Spirit Engineering measures Respiratory protection Hand protection Eye protection Skin protection</p>	<p><b>EXPOSURE CONTROLS AND PERSONAL PROTECTION</b> <b>Workplace exposure limits (WELs)</b> 8 hour TWA 15 min STEL 100 ppm Ensure there is sufficient ventilation of the area. If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required. Protective gloves. Wear safety glasses if there is a risk of eye contact. Protective overalls.</p>			

**SECTION 9**

State: Liquid  
Colour: Colourless

**PHYSICAL AND CHEMICAL PROPERTIES**

Odour: Characteristic Solubility in water: Insoluble S.G. 0.8  
Flash point °C: 40 Flammability limits: 0.9% – 8.0%

**SECTION 10**

Stability  
Conditions to avoid  
Materials to avoid  
Decomposition products

**STABILITY AND REACTIVITY**

Stable under normal conditions.  
Hot surfaces. Sources of ignition. Flames.  
Strong oxidising agents. Strong acids. Strong bases.  
Combustion will generate oxides of carbon, acrid smoke and irritating fumes.

**SECTION 11****Routes of exposure:****TOXICOLOGICAL INFORMATION**

Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting.  
Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.  
Small amounts of liquid aspirated into respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

**SECTION 12****ECOLOGICAL INFORMATION**

Should not be discharged directly in concentrated form to water courses. Toxic to aquatic organisms.

**SECTION 13**

Disposal operations

**DISPOSAL CONDITIONS**

Contact licensed waste disposal company.  
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14**

UN no: 1993  
Shipping name:  
IMDG/IMO EmS: F-E,S-E\*

**TRANSPORT INFORMATION**

Class: 3 PG: III Labelling: 3 ADR/RID Classification code: F1 Hazard ID no: 30  
Flammable Liquid, n.o.s. (White Spirit)  
IATA/ICAO Packing Instructions: 309 (P&CA); 310 (CAO) Tariff Number: 3208 20 90

**SECTION 15**

Hazard symbols  
Contains:  
Risk phrases



Safety phrases

**REGULATORY INFORMATION**

Harmful Dangerous for the environment  
White Spirit  
R10: Flammable.  
R65: Harmful: may cause lung damage if swallowed.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.  
S2: Keep out of the reach of children.  
S24: Avoid contact with skin.  
S37: Wear suitable gloves.  
S51: Use only in well-ventilated areas.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.  
S62: If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label.

**SECTION 16****OTHER INFORMATION**

Always use in accordance with manufacturer's directions.  
Dated 27/06/12 Rev.1

**TERO TECH** Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

**TERO TECH** is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

