

Storm Seal

Easy to apply rapid response roof waterproofing



The last word in easy to apply, rapid response roof waterproofing

What is Storm Seal?

Storm Seal is a bitumen solution that can be quickly and easily sprayed on to any kind of roofing material quickly to produce a thick, instantly waterproof seal even in emergency conditions. No heating, brushing or trowelling is needed – just aim and spray! It can even be used to repair worn or leaky gutters and rainwater outlet systems, or used as a waterproof undercoating.

How does Storm Seal work?

Storm Seal is a unique foaming bitumen solution that can be applied to virtually any roofing surface in temperatures from -5oC up to 40oC, without special tools or training. It achieves a high build rapidly and adheres even to lead and other metals securely.

Key Features and Benefits of Storm Seal?

Just spray on to any roofing surface ideal where access is difficult

Expands rapidly after spraying, achieving a high build quickly

No heating, brushing or trowelling

Apply in nearly any temperature

Can be used with reinforcement sheets to strengthen weak areas

Instantly waterproof

Goes on quickly and evenly in one pass

Technical Information

Storm Seal can be applied quickly to provide emergency waterproofing or waterproofing reinforcement to almost any roofing material, including felt, asphalt, slate, tile, profiled sheet, cement, concrete, lead and other metals. Can be used as an effective waterproof underseal for metal underbody surfaces including gutters and rain spouts.

For your protection, always read the MSDS sheet for Storm Seal before use and follow it closely.

TEROTECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECHTECH** is a registered trademark and subsidiary of **IM Group**.

