










Supercover

Roof coating

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.

	SECTION 1 Product name Product use	PRODUCT IDENTIFICATION Supercover Roof repair compound.	
	SECTION 2 Classification 1272/2008/EC	HAZARDS IDENTIFICATION Physical and Chemical Hazards Human health Environment Contains: White Spirit; Xylene	Flam. Liq. 3, H226 Acute Tox. 4; H312+332; Sk. Irrit. 2; H315; STOT RE2, H373 Aquatic Chronic 2, H411
	Signal word: Warning Hazard symbols:	H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation H332 Harmful if inhaled. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long-lasting effects	
	Hazard statements:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
	Precautionary statements:	P261 Avoid breathing vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
	Supplemental labelling information	P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P370+378 In case of fire: Use foam, CO2, dry powder, water fog to extinguish. P403+235 Store in a well ventilated place. Keep cool. P501 Dispose of contents/container in accordance with national regulations. EUH066 Repeated exposure may cause skin dryness or cracking.	
	SECTION 3 Hazardous components Chemical Name(s)	COMPOSITION/INFORMATION ON INGREDIENTS Related Information % (w/w) CAS no.	Classification/H-Statements
	White Spirit Xylene	25-50 64742-88-7 10-30 1330-20-7	Flam. Liq. 3, H226; STOT RE1, H372; Asp. Tox. 1, H304; Aq. Chron. 2, H411 Flam. Liq. 3, H226; Acute Tox. 4, H312, H332; Skin Irrit. 2, H315
	SECTION 4 In cases of contact Eyes Ingestion Inhalation Skin	FIRST AID MEASURES Flush with water for 15 minutes. Seek medical advice if irritation persists. Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet. Remove to fresh air for at least 10 minutes. Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream. Seek medical advice if irritation develops.	
	SECTION 5 Extinguishing media Special procedures	FIRE FIGHTING MEASURES Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet. Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down.	