

TS72

Multi-purpose repair system - 10 times the strength of concrete



TS72 is an indispensable product that can repair floors, walls and even bond steel.

What is TS72?

TS72 is an indispensable product that can repair floors, walls and even bond steel. Once cured TS72 is 10 times the strength of concrete and can be poured or troweled onto surfaces as required.

TS72 is suitable for use on almost anything that requires a high-quality repair solution due to its ability to bond with any substrate and its taint-free formulation.

Use TS72 on floors, bund walls, stair nosings almost anywhere that requires a strong but attractive finish. TS72 comes in a range of colours.

How does TS72 work?

TS72 comes as a two-pack epoxy formulation which makes it both extremely easy to use as well as being incredibly tough.

Key Features and Benefits of TS72

10 times the strength of concrete.

Two-pack epoxy makes it simple and economical to use.

Multi-purpose product – use on floors, walls, joints, TS72 will bond with all substrates.

Resistant to chemicals.

Long shelf life.

Can be used as a non-slip surface where required.

TS72 can be feather edged

Easy to clean and suitable for food preparation areas.

Pour or trowel onto surfaces as required.

Available in a range of colours.

Technical Information

Mixed pot life: 30 minutes

Curing time: 18 hours

Application temperature: min. 5C

Service temperature: Max 84C

Coverage: 1 square metre at 5mm per pack

Compressive strength (After 7

days): 72N/mm² (Concrete 30)

Tensile strength (After 7 days):

15N/mm² (Concrete 30)

Flexural (After 7 days): 18N/mm² (Concrete 35)

Always ensure that precautionary measures found in the MSDS sheet for TS72 are read and followed before use.

TERO TECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143, Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECH TECH** is a registered trademark and subsidiary of **IM Group**.

