



FIREBLOCK

For sealing holes, cracks and gaps.



What is Fireblock?

Fireblock is a highly versatile, rigorously tested material, compatible with all building products. Fireblock conforms to the following British Standards: B.S. 476 Part 4 1970 Non-Combustible BS 476 Part 8 1972 Indicative 6 hours. Fireblock can be applied in a range of methods including, trowelled, gunned or poured depending on your requirements.

How does Fireblock work?

When mixed with water Fireblock reacts to form a solid tight-knit matrix. During the curing process Fireblock expands by 1% ensuring total adhesion with surrounding substrates. Once fully cured, Fireblock becomes impervious to water, gas, toxic fumes and FIRE.

Key features and benefits of Fireblock

- Permanent 'Fireblock' in one hour.
- Fire tested to rigorous standards.
- Drill it, saw it, cut it – Fireblock can also be easily removed.
- No slump.
- Can be applied in a variety of methods depending on requirements.
- Unaffected by humidity.
- Fireblock will not affect cable insulation or corrode metal pipes.
- Reduces heat loss and increases energy efficiency.
- Protects buildings and saves lives.
- Hardwearing, superior performance.
- Resists oil, petrol and detergents as well as dilute acids and alkalis.

Technical Information

Usable Life: Up to 30 minutes after mixing.
Curing time: 2-8 hours depending on mixing.
Yield: 200ins3 (3277cm³) per 5 litre or 1200ins3 per 30 litres.
Shelf life: 12 months minimum.
Mix Fireblock with water to achieve the required consistency. Pour for horizontal application. Gun or trowel for vertical application.

Always ensure that precautionary measures found in the MSDS sheet for Fireblock are read and followed before use.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.