

QUICK PATCH

Quick Patch is an amazing floor repair material that sets in minutes and adheres to a wide range of building materials.



Quick Patch

Quick Patch is a single use substrate repair patch for a wide range of building materials including concrete, metal and asphalt. Use Quick Patch to repair crumbling brickwork, loose bolt fixings, posts, cracked floors, trip hazards and ramps. Quick Patch is exceptionally strong and hard wearing and is ready to use after simply mixing with water. Either pour or trowel on Quick Patch and your repair will become permanent in minutes.

How does Quick Patch work?

The quantity of water in the mix is not critical meaning this exceptional repair material can be used for many applications.

Mix to a firm consistency to repair overhead or vertical surfaces. Pour a self levelling fluid mixture into horizontal areas. Trowel to finish. Ideal for repairing ramps or making trip hazards safe in walkways.

Key Features and Benefits of Quick Patch?

- Sets as a permanent repair in minutes.
- Highly durable – high levels of tensile strength.
- Can be applied in freezing conditions.
- Ideal for freeze/repairs.
- Just add water and apply.
- Even works in damp and wet conditions.
- Either pour or trowel onto area for repair.
- No solvents.
- Use on concrete, brickwork, stone and asphalt.
- Repair walls, floors, columns, loose posts and bolt fixings.
- Setting times can be altered by mixing hotter or colder water, speeding up cure or allowing more time to form a repair dependent on circumstances

Technical Information

Working time: 4-6 minutes

Setting time: 8-12 minutes

Compression strength (at 20°C): 15N/mm² after 45 minutes, 23N/mm² after 1 hour, 47N/mm² after 24 hours 54N/mm² after 7 days, 50N/mm² after 28 days

Bond strength (slant shear): 40N/mm²

Non flammable

Minimum application

temperature: down to -20°C

Coverage: .25 m² at 4.5mm depth per pack

Average water addition: 0.15 litres per 2.5kg pack

Coefficient of Thermal Expansion: 11x10⁻⁶/°C

Density: 2.200kg/m³

Always ensure that precautionary measures found in the MSDS sheet for Quick Patch are read and followed before use.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.