

SUPERFLEX SMOOTH

A great looking and long lasting waterproofing and crack repair solution for any kind of roofing.



What is Superflex Smooth?

Superflex Smooth is an attractive and highly durable waterproofing and repair compound that can be expected to provide leak-proof roof repairs that last ten years. It bonds to virtually any roofing material, and is available in three colours to match your existing material. Better still, it can be quickly and easily applied even in the wet.

How does Superflex Smooth Work?

Superflex Smooth is a high performance acrylic polymer that forms a watertight, flexible barrier over any kind of roof, including asphalt, felt, concrete and asbestos.

It can even be used to repair leaking skylights and other fixtures as it bonds equally well to lead, iron and other metals, glass and glazing bars, even gutters and downspouts.

Key features and benefits of Superflex Smooth

- Fast and easy to use – no mixing and no priming required.
- Repairs last for up to ten years.
- Bonds to any common construction and roofing material.
- Can be applied with a brush, trowel or roller.
- **Available in three colours:**
 - Black and slate colours blend in with common roofing types and encourage snow and ice to melt quickly.
 - White finish reflects solar heat, lowering your summer energy bills.
 - Excellent shelf life, even after opening the tin.

Technical Information

Superflex Smooth is touch dry approximately 4 hours after application, will accept an overcoat after 16 hours, and can withstand normal foot traffic after 24 hours. Remove all moss, lichen and loose material before applying.

Coverage is 1.5 m² per kilo for most smooth roof surfaces. Available in white, slate or grey. Use with Superflex High Build to fill and reinforce larger cracks and holes.

For your protection, always read the MSDS sheet for Superflex Smooth before use and follow it closely.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.