









META-LUBE PLUS

A Chain and General Purpose Lubricant spray with PTFE micro-suspension

In compliance with Chip 4 and ACOP Compilation of Safety Data Sheets, 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and safety or other such regulations. Risk Assessments require consideration of other information related to the precise circumstances and situation in which a substance or preparation is to be used. Such information is not available to the supplier/compiler of this data.

SECTION 1 Product name Product Use	PRODUCT IDENTIFICATION Meta-Lube Plus A chain and general purpose lubricant spray.																				
SECTION 2 Classification 1272/2008/EC Human health Environment Hazard symbols: Hazard statements: Precautionary statements:	HAZARDS IDENTIFICATION Physical and Chemical Hazards Sk.Irrit.2;H315; STOT SE3;H336 Aquatic Chronic 2; H411 Signal word: Danger Contains: Distillates (Petroleum) Hydrotreated Light Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Avoid breathing vapour/spray. Do not release to the environment. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Dispose of contents/container in accordance with local/national regulations.				Flam. Aerosol 1, H222	   															
SECTION 3 Hazardous components	COMPOSITION <table><tr><th>Related In % (w/w)</th><th>CAS no.</th><th>Classification</th><th>H-Statements</th></tr><tr><td>Distillates (Petroleum)</td><td>50-70</td><td>Asp. Tox. 1; Sk.Irrit.2; STOT SE 3; Aq.Chron. 2</td><td>H304; H315; H336; H411</td></tr><tr><td>Hydrotreated Light</td><td>64742-47-8</td><td>Flam.Gas 1; Gas under pressure</td><td>H220; H280</td></tr><tr><td>Liquefied Petroleum Gas</td><td>10-30</td><td>68476-85-7</td><td></td></tr></table>				Related In % (w/w)	CAS no.	Classification	H-Statements	Distillates (Petroleum)	50-70	Asp. Tox. 1; Sk.Irrit.2; STOT SE 3; Aq.Chron. 2	H304; H315; H336; H411	Hydrotreated Light	64742-47-8	Flam.Gas 1; Gas under pressure	H220; H280	Liquefied Petroleum Gas	10-30	68476-85-7		
Related In % (w/w)	CAS no.	Classification	H-Statements																		
Distillates (Petroleum)	50-70	Asp. Tox. 1; Sk.Irrit.2; STOT SE 3; Aq.Chron. 2	H304; H315; H336; H411																		
Hydrotreated Light	64742-47-8	Flam.Gas 1; Gas under pressure	H220; H280																		
Liquefied Petroleum Gas	10-30	68476-85-7																			
SECTION 4 In cases of contact Eyes Ingestion Inhalation Skin	FIRST AID MEASURES Flush with water for 15 minutes. Seek medical advice if irritation persists. Do not induce vomiting. Give water to drink. Seek medical advice. Remove to fresh air, keep warm, and seek medical advice. Wash with soap and water. Seek medical advice if irritation develops.																				
SECTION 5 Extinguishing media Special procedures	FIRE FIGHTING MEASURES Use Carbon Dioxide, Dry Powder or Foam. Use water spray to keep containers cool. Irritating fumes may be produced in a fire. Wear self-contained breathing apparatus for chemical fires.																				
SECTION 6 Clean-up procedures	ACCIDENTAL RELEASE MEASURES Do not discharge into drains or rivers. Spillage presents a slip hazard. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.				