



META-LUBE PLUS



A Chain and General Purpose Lubricant spray with PTFE micro-suspension



Meta-Lube Plus is a semi-synthetic lubricant with a wide range of applications. It will not corrode or attack sensitive surfaces.

How does Meta-Lube Plus work?

The advanced formulation creeps right into the mechanism, including chains and cables, covering the whole surface area thus eliminating dry spots.

Meta-Lube Plus gets there and stays there! It will cling tenaciously to any surface, even at high revolutions, and creep under moisture - drying it out. The synthetic base fluids then encapsulate the surface and protect against future ingress.

Meta-Lube Plus Technical information

As with other lubricants in the Metalyte range Meta-Lube Plus is as safe as possible to use.

Meta-Lube Plus can be used almost anywhere. All static and moving mechanical parts, drive shafts, slides, pulleys, gears, windows, doors, hinges, press tools, chain drive equipment, escalators, conveyors, fork lifts, chain saws, hoppers, wires, winches, drag lines etc, on indoor and outdoor applications.

Meta-Lube Plus is a powerful, hard working NLGI Grade 2 lubricant, which helps reduce friction wear, corrosion, maintenance and down- time.'

Key Features of Meta-Lube Plus

The formulation will operate over a very wide temperature range (-40°C to 210°C).

Meta-Lube Plus aerosol has an 80% product fill which makes it a very cost effective lubricant.

Meta-Lube Plus is totally non aggressive and can be used on nearly all surfaces and substrates.

Metalyte Riverside Ind. Estate Fazeley, Tamworth Staffordshire B78 3RW

Telephone: 01827 283322 Fax: 01827250143 Metalyte Pipeworks is a wholly owned subsidiary of the IM Group

