

AQUA-KLEN

What is Aqua-Klen?

Aqua Klen is a superb polypropylene absorbent which removes oil quickly and safely, even when the oil is floating on top of a water source. It comes in a range of lightweight shapes and sizes, is easy to use and safe to dispose of.

What can Aqua Klen be used for?

Virtually anything! Under and around machines, petrol and oil pumps. Use to sit drums on. To surround manhole covers to prevent the oil seeping into the drain system. To isolate areas on open water to prevent the oil from spreading further afield, then to absorb the oil to prevent contamination of waterways and water supply. Or as a mat to sit drums and tools on.

Key features and benefits of Aqua-Klen

- Absorbs very quickly.
- Will float on water indefinitely.
- Lightweight and easy to use.
- Absorbs oil and other non-aqueous.
- solvents on contact.
- Dustless and re-usable up to the point of saturation.
- Wide temperature range.
- Can be incinerated, but in itself will not sustain flame.
- Indefinite shelf life.
- Clean and white.
- Very cost effective.

Aqua-Klen technical information

Pads: 46cm x 46cm x 1cm or 46cm x 46cm x 0.5cm
For use on minor spills, around engines, hydraulics and motors. They may be squeezed out and re-used.

Booms: 3m x 13cm. For pick up or containment.
The booms are made of shredded polypropylene encased in an open weave tube. Booms are supplied with harness and clips for towing and can be joined together to form any length to fit outlets, ditches, estuaries, harbours or rivers.

Rolls: 90cm x 40m x 0.5cm. Can be cut to size to accommodate any situation.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.