

AQUA STICK

A product that will actually cure "under-water"

What is Aqua Stick?

Aqua Stick is quite remarkable. Not only will it set in damp, wet or humid conditions but its formulation allows it to actually cure underwater. It will effect a repair in either fresh or salt water and onto almost all substances: fibre-glass, metal, wood, concrete, ceramics, glass or plastic.

How does Aqua Stick work?

Aqua Stick is a two part epoxy which comes in a tube. There is no complicated mixing procedure and Aqua Stick will always cure.

Aqua Stick requires no heat, simply mix and apply. Gone is the necessity to shut down and cover if welding is required. Downtime is kept to a minimum.

Applications

Tanks, tubing, fuel containers, drums, battery cases, electrical connections, sinks, urinals, baths, swimming pools, grooving, cuts, gouges, boat decks and hulls, piping etc.

Key features and benefits of Aqua Stick

Aqua Stick is as permanent as you want it to be. Aqua Stick's compressive strength is an incredible 12,000 psi and once cured can be treated in the same way as the parent substrate in that it can be sanded, painted, drilled, filed, moulded and tapped.

Aqua Stick will bond onto almost any surface; metals, concrete, fibreglass, wood, ceramic, glass, plastics, tiling, etc.

Aqua Stick will hold its shape and form. There is no need to shutter or support the repair whilst waiting for it to cure.

Once cured Aqua Stick will not shrink or lose its original colour. It remains clean and white indefinitely.

Aqua Stick technical information

Working Life: 20 mins

Shelf Life: 1 year

Shore D Hardness: 75

Lap shear strength: 700 psi

Temperature range

a) **Continuous:** 250°F

b) **Intermittent:** 300°F

Electrical resistance: 30,000 megohms

Dielectric strength: 300 volts/mil

Non volatile content: 100%

Compressive strength: 12,000 psi

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.