

DURABRADE

A multi-purpose stripping agent.

Why use Durabrade?

Durabrade is easy to use and cleans without leaving contaminants. Effective on all rigid materials. Abrasive is dispersed throughout the strip, not just on the surface. Removes varnish and epoxy paints. Durabrade will not "load up" and clog. Simply knock out or wash clean.

Where to use Durabrade

Durabrade is ideal for removing rust, scale, light weld splatter and all types of paints from metal surfaces.

It can be used to remove imperfections in hydraulic rams, cylinders, valves and shafts. Durabrade gives a bright finish on all types of metal. Durabrade will remove all types of contaminants and when used correctly, leaves even the most delicate surface undamaged.

Durabrade can be used to prepare materials as diverse as timber, fibreglass, aluminium, ceramics, and stainless steel for further treatment or coating.

Key features and benefits of Durabrade

- Will not "load up" and clog
- Use wet or dry
- Easy to use
- Strong and flexible
- Leaves a smooth finish
- 10 metres per roll
- Easy to clean.
- Available in a variety of grades, Durabrade 60,180 and 400 grit.
- High abrasive silicone carbide.
- Long-lasting - use both sides.

Durabrade Technical Information

Available in 60 grit, 180 grit and 400 grit.
Rolls are 38mm by 10 metres long.

Easy to tear to length.

Encapsulated silicone carbide abrasive system.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.