

## GREASE GUN IN A CAN

The versatile penetrant and lubricant.

### What is Grease Gun in a Can?

This unique product initially sprays a thin penetrating liquid that converts to a grease film and coating within minutes, due to product reaction with air.

The grease film is impervious to salt and moisture and is stable at temperatures up to 200°C. It will lubricate and prevent rust on any metallic surface.

The grease has a tenacious bond to metal and will not rub or wear off as do other penetrating oils or silicone lubricants.

### Grease Gun in a Can preparation for use

Make sure that the aerosol can is not too cold. Shake the can vigorously for 1 to 2 minutes to enable the ball bearing inside the can to mix the grease with the solvent. Spray the mixed product which will penetrate and then dry into a highly effective grease.

### Key features and benefits of Grease Gun in a Can

- Penetrating liquid forms a tack free grease.
- Protective coating in both interior and exterior jobs.
- Convenient application.
- Has excellent pressure resistance.
- Excellent resistance to salt water.
- Heat resistance to 200°C.
- Bonds well to metal surfaces and does not wear off.
- Eliminates down time due to rust and corrosion.
- Excellent release agent.

### Recommended For Use On

Cars  
Aircraft  
Industrial Machinery  
Construction Equipment  
Farm Machinery  
Boats

### Used By:

Maintenance Workshops  
Sewage Departments  
Water Departments  
Oil and Petrol Pipe Lines  
Water and Oil Well Drillers  
Refineries  
Fishing Fleets  
Drag Line Operators  
Printing Companies  
Textile Mills

**IMG Distributors** Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.