

Telephone: (44)01827 255719
Email: distributors@img-limited.co.uk
Industrial Maintenance Group Distributors
Riverside Industrial Estate
Fazeley, Tamworth
Staffordshire. B78 3RW

LIQUID ARMOUR

Old and weather worn machinery and metal surfaces need restoration and recoating at intervals to prolong their useful life and Liquid Armour is the perfect solution.

What is Liquid Armour?

An easy to use, single pack high build epoxy coating that can be applied by brush or roller to previously rusty surfaces.

First brush off loose rust and apply Metalyte Rust Arrester, then simply cover the entire area with Liquid Armour Epoxy encapsulation.

Key features and benefits of Liquid Armour

Liquid Armour has been specifically formulated to be simple to use whilst maintaining much of the superior performance associated with sophisticated two pack epoxies.

The main benefits of using Liquid Armour:

- Touch dry in 2 hours.
- Will adhere to practically any surface.
 - No mixing.
 - Designed for application to badly corroded surfaces.
- Existing painted surfaces can be completely encapsulated.
- Hard wearing durability, even in extreme conditions.
- High resistance to most chemicals including oil, petrol, concentrated detergent, dilute acids and alkalis and corrosive gases.

Liquid Armour technical information

Coverage: up to 15m² per litre. Curing: touch dry in 2 hours. Shelf Life: minimum 12 months.

Colours: Available as standard in Black, White, Red, Yellow, Green and Grev.

Green and Grey.

BS 4800 colours can be supplied but may be subject to a minimum manufacturing quantity of 10×5 litres.

IMG Distributors Riverside Ind. Estate. Fazelev, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.