

Liquid Silk

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product Identifier**
 Material name : Liquid Silk
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
 Product use : Polish, lubricant, mould release agent.
- 1.3 Details of the supplier of the safety data sheet**
 Manufacturer/Supplier: IMG Ltd.,
 Unit M
 Riverside Industrial Estate
 Fazeley
 Tamworth
 B78 3RW
- Tel. : 01827 283322
 Fax. : 01827 250143
- Email (for SDSs) : sales@img-limited.co.uk
- 1.4 Emergency tel. no.:** 01827 283322 (Available from 08.30 – 17.00 hours).

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Physical and Chemical Hazards	Flammable Aerosol Category 1; H222; H229
Human health	Sk.Irrit.2; H315; STOT SE3; H336
Environment	Aq.Chron.2; H411

2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC

Signal word: Danger

Contains: Naphtha (Petroleum) Hydrotreated Light

Pictograms:



Hazard Statements:	H222 H229 H315 H336 H411	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Precautionary Statements:	P210 P211 P251 P410+P412 P261	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Avoid breathing vapour/spray.