

Telephone: (44)01827 255719
Email: distributors@img-limited.co.uk
Industrial Maintenance Group Distributors
Riverside Industrial Estate
Fazeley, Tamworth
Staffordshire. B78 3RW

# LIQUID SILK

## A high performance silicone with added shine.



## What is Liquid Silk?

Liquid Silk is an amazing multipurpose silicone spray that can stop sqeaks, polish leather and provide a non-stick water repellent surface for industrial, commercial and household purposes. Liquid Silk is colourless and odourless and formulated to withstand temperatures up to 300c

#### Areas of use

As a lubricant and release agent to prevent sticking hinges, locks, bolts, and machinery parts. Use Liquid Silk to give a protective shield for the easy removal of food, paint, adhesives, ink and more. The water repellent properties of Liquid Silk mean it can also be used to prevent corrosion on light bulls occlets and battery terminals.

Always ensure that precautionary measures found on the MSDS sheet for Liquid Sik, are read and followed before

Use on leather, wood, rubber and plastic to bring a high shine finish to cleaning tasks.

### Key features of Liquid Silk

- Use as a lubricant, polish, water repellent and protector.
- Colourless and odourless Liquid Silk won't stain.
- High temperature resistance of up to 300c.
- Can be used with an extension tube for hinge or machinery lubrication and as a spray for release and polishing tasks.

## How to get the best results

When using as a polish or water repellent, simply spray onto surface and polish with a clean dry cloth. When using as a lubricant or release agent, use the extension tube to direct the product to the specific area. n.b. Take care not to allow overspray to create a slippery floor surface.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group structly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept flability for more than product replacement.