

Telephone: (44)01827 255719
Email: distributors@img-limited.co.uk
Industrial Maintenance Group Distributors
Riverside Industrial Estate
Fazeley, Tamworth
Staffordshire. B78 3RW

RUST BYTE

Rust Byte is a deep white penetrant for the quick release of seized and corroded parts.

What is Rust Byte?

Rust-Byte is a pure synthetic lubricant. Once applied it stays there leaving plant and equipment in a totally reusable condition. There is hardly any 'product evaporation'.

Rust-Byte is safe to use. It is nonconductive and has no mineral oil content.

How does Rust Byte work?

Rust Byte penetrates quickly and effectively. Rust-Byte speeds through layers of grease, rust. lead deposits and sludge. The penetration continues until the lubricant has reached the heart of the problem.

Rust Byte works quickly, reducing labour costs.

Areas of use

Here are some of the following industries that best highlight Rust Byte's key uses.

Chemical

Turbines, regulators, heat exchangers, conveyor belts, bolts, etc.

Shipping

Generators, anchor winches, fittings, bilge pump assemblies, winches, exhaust heads, propeller removal, etc.

Automotive

Exhaust pipes, bolts, nuts, clutch housings, manifold gaskets, battery terminals, spark plugs, speedometer cables, cables, hose connections, clutch assemblies, etc.

Building

Track adjustments, bucket elevators, pumps, compressors, pipe fittings, etc.

Seneral

Cap screws, flange bolts, conveyors, drill holes, boiler fittings, boiler face plates, manhole covers, pipe threads, shut off valves, etc.

Farming

Snap couplings, pivot pins, lift controls, guide pins, end cap bolts, nozzle threads, running gears, etc.

Always read the Safety Data Sheet.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group structly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept flability for more than product replacement.