

UNIWRAP

Uniwrap, the textured elastic strap used to wrap around pipes and contain emergency leaks.

What is the Uniwrap?

Uniwrap is a highly strengthened ethylene propylene diene monomer (EPDM) strap textured to grip when wrapped round pipework, finishing with a velcro attachment to maintain the pressure.

Uniwrap is able to be stretched to 6 times its original length and is used to create seals, even on leaks in the most difficult circumstances.

Uniwrap will seal pipework up to 8 bar and can be used on tees, elbows as well as straight runs. Uniwrap has been developed to be used in conjunction with our epoxy sticks, please see our Titan Seal kits. By compressing the epoxy into live defects, it provides the mechanical force to overcome pressure whilst the epoxy cures, ensuring a seal to cracks, holes and leaks.

How does Uniwrap work?

epoxy is cured the Uniwrap can be removed after the leak has been sealed and the area overwrapped with one of our composite repair wraps. Uniwrap can also be overwrapped with Cayman Rapid to create a long lasting repair.

Key features and benefits of Uniwrap

Applications

Leak stopping on all pipe geometries. Use with epoxy sticks and Cayman Rapid.

Benefits

Instant leak stopper.
Designed specifically for use with epoxy sticks.
Fast deployment and lightweight.
Reusable and adaptable.
Provides both short and long term solutions.

Uniwrap technical information

Mechanic Properties

Elongation 600%

Temperature -40°C to +70°C

Health and Safety

Always ensure that precautionary measures found in the MSDS sheet for Uniwrap are read and followed before use and please ensure that appropriate PPE is used when preparing, mixing and applying products.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.