

# FOAMSEAL CLEANER

## Cleaner for Foamseal gun equipment

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.



### SECTION 1

Product name  
Product Use

**PRODUCT IDENTIFICATION**  
Foam Seal Gun Wash  
Cleaner for Foamseal gun equipment.



### SECTION 2

Classification 127/2/2008/EC

### HAZARDS IDENTIFICATION

Physical and Chemical Hazards  
Human health  
Not classified

Flam. Aerosol 1, H222  
Eye Irrit.2; H319; STOT SE3, H336; EUH066



Environment  
Hazard symbols:  
Hazard statements:

Signal word: Danger

Contains: Acetone  
Extremely flammable aerosol.  
Pressurized container: May burst if heated.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Keep away from heat/sparks/open flames/hot surfaces – No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn even after use.  
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Avoid breathing vapours/spray.  
Wear eye protection/face protection.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
If eye irritation persists get medical advice/attention  
Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

H222  
H229  
H319  
H336  
P210  
P211  
P251  
P410+412  
P261  
P280  
P305+351+338

Supplemental label information:

P337+313  
EUH066



### SECTION 3

Hazardous components

**COMPOSITION**  
Related in  
% (w/w) CAS no.  
30-70 67-64-1  
10-30

**Classification**  
Flam.Liq. 2; Eye Irrit.2; STOT SE3  
Flam.Gas 1  
Gas under pressure

**H-Statements**  
H225; H319; H336; EUH066  
H220  
H280

Acetone  
Liquefied Petroleum Gas



### SECTION 4

In cases of contact  
Eyes  
Ingestion  
Inhalation  
Skin

### FIRST AID MEASURES

Flush with water for 15 minutes. Seek medical advice if irritation persists.  
Do not induce vomiting. Give water to drink. Seek medical advice.  
Remove to fresh air, keep warm, and seek medical advice.  
Wash with soap and water. Seek medical advice if irritation develops.



### SECTION 5

Extinguishing media  
Special procedures

### FIRE FIGHTING MEASURES

Use Carbon Dioxide, Dry Powder or Foam.  
Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool.



### SECTION 6

Clean-up procedures

### ACCIDENTAL RELEASE MEASURES

Eliminate all sources of ignition. Do not discharge into drains or rivers. Absorb into dry earth or sand.  
Transfer to a closable, labelled salvage container for disposal by an appropriate method.