



FOAMSEAL CLEANER

Cleaner for Foamseal gun equipment

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.



SECTION 1

Product name
Product Use

PRODUCT IDENTIFICATION

Foam Seal Gun Wash
Cleaner for Foamseal gun equipment.



SECTION 2

Classification 1272/2008/EC

HAZARDS IDENTIFICATION

Physical and Chemical Hazards Flam. Aerosol 1, H222
Human health Eye Irrit.2; H319; STOT SE3, H336; EUH066

Environment

Not classified



Hazard symbols:

Signal word: Danger

Contains: Acetone

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.



Precautionary statements:

P210

Keep away from heat/sparks/open flames/hot surfaces – No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Pressurized container: Do not pierce or burn even after use.

P410+412

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P261

Avoid breathing vapours/spray.

P280

Wear eye protection/face protection.

P305+351+338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

Supplemental label information:

P337+313

If eye irritation persists get medical advice/attention

EUH066

Repeated exposure may cause skin dryness or cracking.



SECTION 3

Hazardous components

Acetone
Liquefied Petroleum Gas

COMPOSITION

Related In

% (w/w)	CAS no.
30-70	67-64-1
10-30	68476-85-7

Classification

Flam.Liq. 2; Eye Irrit.2; STOT SE3
Flam.Gas 1

H-Statements

H225; H319; H336; EUH066
H220

Gas under pressure

H280



SECTION 4

In cases of contact
Eyes
Ingestion
Inhalation
Skin

FIRST AID MEASURES

Flush with water for 15 minutes. Seek medical advice if irritation persists.
Do not induce vomiting. Give water to drink. Seek medical advice.
Remove to fresh air, keep warm, and seek medical advice.
Wash with soap and water. Seek medical advice if irritation develops.



SECTION 5

Extinguishing media
Special procedures

FIRE FIGHTING MEASURES

Use Carbon Dioxide, Dry Powder or Foam.
Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool.



SECTION 6

Clean-up procedures

ACCIDENTAL RELEASE MEASURES

Eliminate all sources of ignition. Do not discharge into drains or rivers. Absorb into dry earth or sand.
Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**SECTION 7**

Handling

Storage

HANDLING AND STORAGE

Ensure there is sufficient ventilation of the area. Smoking is forbidden. Avoid prolonged or repeated contact with skin.

Store in cool, well ventilated area, below 50°C. Keep away from ignition sources.

**SECTION 8**

Hazardous components

Chemical name

Acetone

Butane

Engineering measures

Respiratory protection

Hand protection

Eye protection

Skin protection

EXPOSURE CONTROLS AND PERSONAL PROTECTION

Workplace exposure limits (WELs)

8 hour TWA 15 min STEL

Related information

1210 mg m⁻³ 3620 mg m⁻³1450 mg m⁻³ 1810 mg m⁻³

Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Protective gloves.

Wear safety glasses if there is a risk of eye contact.

Protective overalls.

**SECTION 9**

State: Aerosol

Flash point °C: <0

PHYSICAL AND CHEMICAL PROPERTIES

Odour: Ketone/hydrocarbon

Colour: Colourless

Solubility in water: Miscible

Flammability limits: 0.8% – 13.0%

**SECTION 10**

Stability

Conditions to avoid:

Materials to avoid

Decomposition products

STABILITY AND REACTIVITY

Stable under normal conditions.

Hot surfaces. Sources of ignition. Flames.

Strong acids. Strong bases. Oxidising agents.

Oxides of carbon.

**SECTION 11**

Hazardous ingredients:

Skin

Eye

Ingestion

Inhalation

TOXICOLOGICAL INFORMATION

Acetone

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

Contact may cause irritation and redness. Prolonged or repeated contact may defat the skin leading to dermatitis.

Contact may cause irritation and pain.

Nausea and stomach pain may occur. There may be irritation of the mouth, throat and digestive tract.

May cause upper respiratory tract irritation if high levels of vapour are inhaled.

**SECTION 12****ECOLOGICAL INFORMATION**

The aerosol contents are potentially harmful to aquatic organisms.

**SECTION 13**

Disposal operations

DISPOSAL CONDITIONS

Contact licensed waste disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14**

UN no: 1950

Shipping name: Aerosols

TRANSPORT INFORMATION

Class: 2

Labelling: 2.1

ADR/RID Classification code: 5F

IMDG/IMO EmS: F-D,S-U

Tariff Number: 3814 00 90

**SECTION 15**

Regulatory references:

REGULATORY INFORMATION

Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

**SECTION 16****OTHER INFORMATION**

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.

Always use in accordance with manufacturer's directions.

Dated 26/08/15

CLP/Rev.1

TERO TECH Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

TERO TECH is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

