

MACHINE LUBE

Suitable for Incidental Food Contact.



What is Machine Lube?

Machine Lube is a synthetic lubricant which comprises of PTFE for friction reduction, and the addition of the latest technological additives, to produce a high performance and high temperature lubricant.

Machine Lube is **InS H1 registered** so suitable for incidental food contact in industries classed as “environmentally clean”, such as catering and pharmaceutical.

Areas of use

Machine Lube has excellent resistance to water and steam, which makes it ideal for applications where frequent wash down of plant is essential.

Machine Lube is ideal for lubrication of bearings, slides and all delicate mechanisms used on the food manufacturing & processing industry. Particularly recommended for use in bakery mixing machines, milk and soft drink bottling plants, and food canning plants.

Main Features

- Food grade InS H1 approved formulation is suitable for areas where incidental contact with food may occur.
- Non-Toxic.
- Low odour.
- Maximum operating temperature 150°C.
- Excellent resistance to water, steam, acids & alkalis.
- Suitable for use in plain and anti-friction bearings.
- Exceptional high load ability.
- Excellent adhesion.
- Will lubricate most food factory applications that require grease.
- High temperature performance extends component life and reduces need to re-lubricate.

Technical info

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, take care not to over-lubricate. Only apply the quantity of grease recommended by the bearing manufacturer.

Health and Safety

Always ensure that precautionary measures found in the MSDS sheet for Machine Lube are read and followed before use and please ensure that appropriate PPE is used when preparing, mixing and applying products.

IMG Distributors Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.