

## MACHINE LUBE HD

A multi purpose gel lubricant suitable for use in areas where incidental contact with food may occur.



### Key features

- Non toxic.
- Low odour.
- High temperature performance of -10°C to +150°C.
- Reduces friction and wear.
- INS H1 Registered.
- Translucent and smooth.
- Unworked penetration 265-295

### What is Machine Lube HD?

Machine Lube HD is a translucent non-coloured smooth grease. It is based upon severely refined mineral white oil, gelled with an inorganic thickening system. The latest technology is used to provide a high temperature lubricant that is capable of meeting the most arduous duties on both bearings and gears.

Machine Lube HD exhibits good plastics compatibility and can be used for the lubrication of many plastic components in the automotive industry.

### Areas of use

Machine Lube HD is recommended for use as a general purpose lubricant for plant and equipment, in the processing and packaging of foodstuffs where incidental food contact may occur. The grease is translucent in appearance and can be utilised in many general lubrication situations where a non-coloured product is required.

### How to use

As with all greases used for the first time, check the compatibility with the grease previously used, and if necessary purge the bearing prior to application. Do not over lubricate. Only apply the quantity of grease recommended by the bearing manufacture.

**THIS PRODUCT IS ALSO AVAILABLE IN AN AEROSOL  
ASK YOUR ACCOUNT MANAGER FOR MORE DETAILS.**

### Health and Safety

Always ensure that precautionary measures found in the MSDS sheet for Machine Lube HD are read and followed before use and please ensure that appropriate PPE is used when preparing, mixing and applying products.

**IMG Distributors** Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.