

Easi-Floor (Except Yellow)

Floor coating

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.

	SECTION 1 Product name Product use	PRODUCT IDENTIFICATION Easi Floor (All colours except yellow) Paint															
    	SECTION 2 Classification 1272/2008/EC Signal word: Warning Hazard statements: Precautionary statements: Supplemental labelling information	HAZARDS IDENTIFICATION Physical and Chemical Hazards Human health Environment Contains: White Spirit H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long-lasting effects P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P370+378 In case of fire: Use foam, CO ₂ , dry powder, water fog to extinguish. P403+235 Store in a well ventilated place. Keep cool. P501 Dispose of contents/container in accordance with national regulations. EUH208 Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.															
	SECTION 3 Hazardous components Chemical Name(s) White Spirit 2-Methoxy-1-methylethyl acetate Xylene Ethyl Methyl Ketoxime	COMPOSITION INFORMATION ON INGREDIENTS Related Information <table border="1"> <thead> <tr> <th>% (w/w)</th> <th>CAS no.</th> <th>Classification/H-Statements</th> </tr> </thead> <tbody> <tr> <td>30-60</td> <td>64742-88-7</td> <td>Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411</td> </tr> <tr> <td><1</td> <td>108-65-6</td> <td>Flam. Liq. 3, H226</td> </tr> <tr> <td><1</td> <td>1330-20-7</td> <td>Flam. Liq. 3, H226; Acute Tox. 4, H312, H332; Skin Irrit. 2, H315</td> </tr> <tr> <td><1</td> <td>96-29-7</td> <td>Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Dam. 1, H318; Sk.Sens.1, H317; Cerc.2, H361</td> </tr> </tbody> </table>	% (w/w)	CAS no.	Classification/H-Statements	30-60	64742-88-7	Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411	<1	108-65-6	Flam. Liq. 3, H226	<1	1330-20-7	Flam. Liq. 3, H226; Acute Tox. 4, H312, H332; Skin Irrit. 2, H315	<1	96-29-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Dam. 1, H318; Sk.Sens.1, H317; Cerc.2, H361
% (w/w)	CAS no.	Classification/H-Statements															
30-60	64742-88-7	Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411															
<1	108-65-6	Flam. Liq. 3, H226															
<1	1330-20-7	Flam. Liq. 3, H226; Acute Tox. 4, H312, H332; Skin Irrit. 2, H315															
<1	96-29-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Dam. 1, H318; Sk.Sens.1, H317; Cerc.2, H361															
	SECTION 4 Contact with Eyes Ingestion Inhalation Skin	FIRST AID MEASURES Flush with water for 15 minutes. Seek medical advice if irritation persists. Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet. Remove to fresh air for at least 10 minutes. Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream. Seek medical advice if irritation develops.															
	SECTION 5 Extinguishing media Special procedures	FIRE FIGHTING MEASURES Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet. Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down.															