



Easi-Floor (Except Yellow)

Floor coating

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.



SECTION 1

Product name
Product use

PRODUCT IDENTIFICATION

Easi Floor (All colours except yellow)
Paint



SECTION 2

Classification 1272/2008/EC

HAZARDS IDENTIFICATION

Physical and Chemical Hazards Flam. Liq. 3, H226
Human health STOT SE3, H336; STOT RE2, H373
Environment Aquatic Chronic 2, H411



Signal word: Warning
Hazard statements:

Contains: White Spirit

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long-lasting effects



Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.



P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use foam, CO2, dry powder, water fog to extinguish.

P403+235 Store in a well ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulations.



Supplemental labelling information

EUH208 Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.



SECTION 3

Hazardous components

Chemical Name(s)

White Spirit
2-Methoxy-1-methylethyl acetate
Xylene
Ethyl Methyl Ketoxime

COMPOSITION/INFORMATION ON INGREDIENTS

Related Information

% (w/w)	CAS no.
30-60	64742-88-7
<1	108-65-6
<1	1330-20-7
<1	96-29-7

Classification/H-Statements

Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411
Flam. Liq. 3, H226
Flam. Liq. 3, H226; AcuteTox. 4, H312, H332; Skin Irrit. 2, H315
Flam. Liq. 3, H226; AcuteTox. 4, H312; Eye Dam.1, H318;
Sk.Sens.1, H317; Carc.2, H351



SECTION 4

Contact with
Eyes
Ingestion
Inhalation
Skin

FIRST AID MEASURES

Flush with water for 15 minutes. Seek medical advice if irritation persists.
Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet.
Remove to fresh air for at least 10 minutes.
Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream.
Seek medical advice if irritation develops.



SECTION 5

Extinguishing media
Special procedures

FIRE FIGHTING MEASURES

Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet.
Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down.

**SECTION 6**

Clean-up procedures

ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not discharge into drains or rivers. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**SECTION 7**Handling
Storage**HANDLING AND STORAGE**

Do not eat, smoke or drink whilst working with this material. Wash hands before meals and after work. Store in a cool, well ventilated area. Keep containers tightly closed.

**SECTION 8**

Hazardous components
Chemical name
White Spirit
Engineering measures
Respiratory protection
Hand protection
Eye protection
Skin protection

EXPOSURE CONTROLS AND PERSONAL PROTECTION

Workplace exposure limits (WELs)
8 hour TWA 15 min STEL Related information
100 ppm (Supplier's classification)
Ensure there is sufficient ventilation of the area.
If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.
Protective gloves.
Wear safety glasses if there is a risk of eye contact.
Protective overalls.

**SECTION 9**State: Liquid
Colour: Coloured**PHYSICAL AND CHEMICAL PROPERTIES**

Odour: Characteristic Solubility in water: Insoluble S.G. 1.05-1.15
Flash point °C: >30 Flammability limits: 0.7% – 7.0%

**SECTION 10**

Stability
Conditions to avoid
Materials to avoid
Decomposition products

STABILITY AND REACTIVITY

Stable under normal conditions.
Hot surfaces. Sources of ignition. Flames.
Strong oxidising agents. Strong acids. Strong bases.
Combustion will generate oxides of carbon, oxides of nitrogen, acrid smoke and irritating fumes.

**SECTION 11**

Routes of exposure:

TOXICOLOGICAL INFORMATION

Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases. Small amounts of liquid aspirated into respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

**SECTION 12****ECOLOGICAL INFORMATION**

Should not be discharged directly in concentrated form to water courses. Toxic to aquatic organisms.

**SECTION 13**

Disposal operations

DISPOSAL CONDITIONS

Contact licensed waste disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14**UN no: 1263
Shipping name: Paint**TRANSPORT INFORMATION**

Class: 3 PG: III Labelling: 3 ADR/RID Classification code: F1 Hazard ID no: 33
IMDG/IMO EmS: F-E,S-E Marine Pollutant: No IATA: UN1263 PG III Tariff Number: 32082090

**SECTION 15**

Regulatory references:

REGULATORY INFORMATION

Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

**SECTION 16****OTHER INFORMATION**

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.
Always use in accordance with manufacturer's directions.
Dated 08/07/2016 CLP/Rev.1

TERO TECH Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

TERO TECH is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

