

# EASI-FLOOR

Convenient, single pack floor coating with the superior performance of two-pack epoxies.



## What is Easi-Floor?

Easi-Floor is a simple to use, single pack floor coating. Easi-Floor is available in a range of colours and can be used on any surface. You can even use Easi-Floor as a sealant for concrete or varnish for wooden floor surfaces.

## How does Easi-Floor work?

The innovative Epoxy-Ester based formulation of Easi-Floor means the convenience of a single pack combined with the superior, hardwearing performance associated with two-pack floor coatings.

## Key features and benefits of Easi-Floor

- Convenient single-pack means no mixing.
- Easi-Floor can be used on almost any surface.
- Use Easi-Floor to coat previously painted surfaces without costly removal of existing coatings.
- Surface dry in an amazing 2 hours.
- Floor back to full service within 24 hours.
- Easi-Floor is a multi-purpose product – use it for sealing concrete or varnishing wooden floors.
- Available in a variety of colours.
- Hardwearing, superior performance.
- Resists oil, petrol and detergents as well as dilute acids and alkalis.

## Technical Information

Coverage: Up to 15m<sup>2</sup> per litre (depending on surface porosity)

### Drying times

**Surface dry:** 2 hours (recoatable overnight)

**Fully dry:** 24 hours

**Shelf life:** 12 months minimum

**Porous surfaces:** It is recommended that porous surfaces are sealed with Easi-Floor diluted with a 10% addition of multi-purpose solvent.

**Colours:** Available as standard in Red, Green, Grey and Clear.

BS 4800 colours can be supplied but maybe subject to a minimum manufacturing quantity of 10 x 5 litres.

Always ensure that precautionary measures found in the MSDS sheet for Easi-Floor are read and followed before use.

**IMG Distributors** Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW.

The IM Group utilizes a process of continuous product improvement for all of our products. While the IM Group strictly adhere to our products specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. The IM Group warrants the quality of this product when used according to directions. Apply protective coatings per Company Standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.