




















Easi-Floor (Yellow)

Floor coating

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.

|  | SECTION 1 | PRODUCT IDENTIFICATION | | | | | | | | | | | | | | | | | | |
|---|--|--|---------------------|---------|-----------------------------|---------|--|--|-------|------------|---|------|-----------|--|----|----------|--------------------|----|---------|--|
| | Product name Product use | Easi - Floor (Yellow) Paint | | | | | | | | | | | | | | | | | | |
|  | SECTION 2 | HAZARDS IDENTIFICATION | | | | | | | | | | | | | | | | | | |
|  | Classification 1272/2008/EC | Physical and Chemical Hazards Human health Flam. Liq. 3, H226 Carc.1B, H350; Repr.1A, H361df; STOT SE3, H336; STOT RE2, H373 | | | | | | | | | | | | | | | | | | |
|  | Signal word: Danger Hazard statements: | Environment Contains: White Spirit, Lead Chromate Pigment(s) Restricted to professional users. | | | | | | | | | | | | | | | | | | |
|  | Precautionary statements: | <p>H226 Flammable liquid and vapour.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H350 May cause cancer.</p> <p>H361df May damage the unborn child. Suspected of damaging fertility.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long-lasting effects</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapours/spray.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection</p> <p>P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>P308+313 IF exposed or concerned: Get medical advice/attention.</p> <p>P370+378 In case of fire: Use foam, CO2, dry powder, water fog to extinguish.</p> <p>P403+235 Store in a well ventilated place. Keep cool.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p> <p>EUH 201 Contains Lead. Should not be used on surfaces liable to be chewed or sucked by children.</p> <p>EUH208 Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.</p> | | | | | | | | | | | | | | | | | | |
|  | Supplemental labelling information | | | | | | | | | | | | | | | | | | | |
|  | SECTION 3 | COMPOSITION/INFORMATION ON INGREDIENTS | | | | | | | | | | | | | | | | | | |
| | Hazardous components Chemical Name(s) White Spirit Lead Chromate Pigment(s) | <table> <thead> <tr> <th data-bbox="614 1736 699 1758">Related Information</th> <th data-bbox="708 1736 890 1758">CAS no.</th> <th data-bbox="900 1736 1477 1758">Classification/H-Statements</th> </tr> </thead> <tbody> <tr> <td data-bbox="614 1767 699 1792">% (w/w)</td> <td data-bbox="708 1767 890 1792"></td> <td data-bbox="900 1767 1477 1792"></td> </tr> <tr> <td data-bbox="614 1800 699 1825">30-60</td> <td data-bbox="708 1800 890 1825">64742-88-7</td> <td data-bbox="900 1800 1477 1825">Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411</td> </tr> <tr> <td data-bbox="614 1834 699 1859">5-10</td> <td data-bbox="708 1834 890 1859">1344-37-2</td> <td data-bbox="900 1834 1477 1859">Acute Tox.4, H332; Sk.Irrit.2, H315; Eye Irrit.2, H319; Carc.1B, H350; Repr.1A, H361df; STOT SE3, H335; STOT RE2, H373; Aq.Chron.2, H411</td> </tr> <tr> <td data-bbox="614 1912 699 1937"><1</td> <td data-bbox="708 1912 890 1937">108-65-6</td> <td data-bbox="900 1912 1477 1937">Flam. Liq. 3, H226</td> </tr> <tr> <td data-bbox="614 1946 699 1971"><1</td> <td data-bbox="708 1946 890 1971">96-29-7</td> <td data-bbox="900 1946 1477 1971">Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Dam.1, H318; Sk.Sens.1, H317; Carc.2, H351</td> </tr> </tbody> </table> | Related Information | CAS no. | Classification/H-Statements | % (w/w) | | | 30-60 | 64742-88-7 | Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411 | 5-10 | 1344-37-2 | Acute Tox.4, H332; Sk.Irrit.2, H315; Eye Irrit.2, H319; Carc.1B, H350; Repr.1A, H361df; STOT SE3, H335; STOT RE2, H373; Aq.Chron.2, H411 | <1 | 108-65-6 | Flam. Liq. 3, H226 | <1 | 96-29-7 | Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Dam.1, H318; Sk.Sens.1, H317; Carc.2, H351 |
| Related Information | CAS no. | Classification/H-Statements | | | | | | | | | | | | | | | | | | |
| % (w/w) | | | | | | | | | | | | | | | | | | | | |
| 30-60 | 64742-88-7 | Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411 | | | | | | | | | | | | | | | | | | |
| 5-10 | 1344-37-2 | Acute Tox.4, H332; Sk.Irrit.2, H315; Eye Irrit.2, H319; Carc.1B, H350; Repr.1A, H361df; STOT SE3, H335; STOT RE2, H373; Aq.Chron.2, H411 | | | | | | | | | | | | | | | | | | |
| <1 | 108-65-6 | Flam. Liq. 3, H226 | | | | | | | | | | | | | | | | | | |
| <1 | 96-29-7 | Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Dam.1, H318; Sk.Sens.1, H317; Carc.2, H351 | | | | | | | | | | | | | | | | | | |
|  | SECTION 4 | FIRST AID MEASURES | | | | | | | | | | | | | | | | | | |
| | Contact with Eyes Ingestion | Flush with water for 15 minutes. Seek medical advice if irritation persists. Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet. | | | | | | | | | | | | | | | | | | |

| | | |
|---|---|---|
| | Inhalation Skin | Remove to fresh air for at least 10 minutes. Seek medical advice. Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream. Seek medical advice if irritation develops. |
|  | SECTION 5 Extinguishing media Special procedures | FIRE FIGHTING MEASURES Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet. Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down. |
|  | SECTION 6 Clean-up procedures | ACCIDENTAL RELEASE MEASURES Remove all ignition sources. Do not discharge into drains or rivers. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. |
|   | SECTION 7 Handling Storage | HANDLING AND STORAGE Do not eat, smoke or drink whilst working with this material. Wash hands before meals and after work. Store in a cool, well ventilated area. Keep containers tightly closed. |
|  | SECTION 8 Hazardous components Chemical name White Spirit Engineering measures Respiratory protection Hand protection Eye protection Skin protection | EXPOSURE CONTROLS AND PERSONAL PROTECTION Workplace exposure limits (WELs) 8 hour TWA 15 min STEL Related information 100 ppm (Supplier's classification) Ensure there is sufficient ventilation of the area. Wear a respirator suitable/approved for organic vapours/particulates especially if spraying. Protective gloves approved to EN374. Wear safety glasses if there is a risk of eye contact. Protective overalls. |
|  | SECTION 9 State: Liquid Colour: Yellow | PHYSICAL AND CHEMICAL PROPERTIES Odour: Characteristic Solubility in water: Insoluble S.G. 1.05-1.15 Flash point °C: >30 Flammability limits: 0.7% – 7.0% |
|  | SECTION 10 Stability Conditions to avoid Materials to avoid Decomposition products | STABILITY AND REACTIVITY Stable under normal conditions. Hot surfaces. Sources of ignition. Flames. Strong oxidising agents. Strong acids. Strong bases. Combustion will generate oxides of carbon, oxides of nitrogen, oxides of lead, antimony and chromium, acrid smoke and irritating fumes. |
|  | SECTION 11 Routes of exposure: | TOXICOLOGICAL INFORMATION Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases. Small amounts of liquid aspirated into respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema. Increased incidences of lung cancer have been identified in the chromate pigment manufacturing industry, but there is no evidence of lung cancer arising from the use of products containing lead chromate. All lead compounds are classified as causing developmental toxicity in humans. |
|  | SECTION 12 | ECOLOGICAL INFORMATION Should not be discharged directly in concentrated form to water courses. Toxic to aquatic organisms. |
|  | SECTION 13 Disposal operations | DISPOSAL CONDITIONS Contact licensed waste disposal company. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. |
|  | SECTION 14 UN no: 1263 Shipping name: Paint | TRANSPORT INFORMATION Class: 3 PG: III Labelling: 3 ADR/RID Classification code: F1 Hazard ID no: 33 IMDG/IMO EmS: F-E,S-E Marine Pollutant: No IATA: UN1263 PG III Tariff Number: 32082090 |

**SECTION 15**

Regulatory references:

REGULATORY INFORMATION

Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

**SECTION 16****OTHER INFORMATION**

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.

Always use in accordance with manufacturer's directions.

Dated 08/07/2016 CLP/Rev.1

TERO TECH Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

TERO TECH is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

